

Product Name:	Bluelab Truncheon® Nutrient Meter V2
Product Code:	TRUNV2
UPC Code:	9421024920012
Country of Origin:	New Zealand
Tariff Code:	9027.80
Shipping Quantity:	Sold as singular unit
Packaging Information:	
Packaged Weight:	0.28 kg / 0.617 lb
Packaged Length:	415 mm / 16.34 in
Packaged Width:	40 mm / 1.574 in
Packaged Height:	40 mm / 1.574 in

Sales Description:
NOTE: this copy can be used in brochures, catalogues or online

The globally respected conductivity meter, simply brilliant, durable, reliable

Displaying all the conductivity scales EC, CF, PPM 500 & PPM 700 on a single line.

Each time you feed your plants it's essential to know the nutrient levels of your solution. Simply done with the Bluelab® Truncheon® Nutrient Meter.

Flashing lights indicate your conductivity reading, which is automatically compensated with the integrated temperature sensor. Removable shroud for easy cleaning.

Meter length: 40cm / 16 in.

Features

- Conductivity range up to 3.6 EC, 36 CF, 1800 ppm 500 and 2520 ppm 700
- Fully waterproof
- Provided with EC, CF, ppm 700 and ppm 500 scales
- Auto on/off function
- No calibration required (factory calibrated)
- Daylight readable blue LEDs, visible in bright or dark environments
- No buttons or switches
- Battery operated (3x AA batteries included)
- Measure while mixing nutrients in your reservoir

Product Guarantee:

Five year free repair or replacement guarantee.



Product Image:



Product images available for Screen or Web use:

- Bluelab-TruncheonV2-MR-flat-RGB.jpg
- Bluelab-TruncheonV2-MR-WEB
- Bluelab-TruncheonV2-MR-WEB-Sml

Product images available for PRINT:

Note: these images are high resolution in CMYK.

- Bluelab-TruncheonV2-MR-flat-CMYK.tif

Technical Specifications:

Measurement Range:	0.2 – 3.6 EC, 2 – 36 CF 100 – 1800 ppm (EC x 500) 140 – 2520 ppm (EC x 700)
Resolution:	0.1 EC, 1 CF 50 ppm (EC x 500) 70 ppm (EC x 700)
Accuracy at 2.77EC and 25°C / 77°F:	± 0.1 EC, ± 1 CF ± 50 ppm (1385 ppm at 500 ppm) ± 70 ppm (1939 ppm at 700 ppm)
Automatic Temperature Compensation:	Yes
Operating Environment:	0 – 50°C / 32 – 122°F
Calibration:	Not required
Power Source:	3 x AA alkaline batteries
User Manual Languages Available:	English; Español; Français-Canada; Nederlands; Deutsch
Certifications:	CE and FCC

{This Product Information Sheet is NOT intended for distribution to end users.}